



SKB900N-A 2 Glass Door Display or Storage Fridge

Model ID: SKB900N-A

A bottom mount ActiveCore 2 with a host of design choices. 880 litres of eye-level display space meets an extensive list of options to tailor the fridge to your business.



5 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Customize your fridge to suit your space - add shelf lights or stainless steel shelves for a premium look
- Door options - solid doors, heated glass doors to prevent condensation in hot environments, Gen-3 series look
- Save time restocking with 60 product facings (600ml PET bottle)
- Reduce power bills and boost your environmental credentials with market-leading natural refrigerant technology that has virtually no impact on the environment
- Minimize waste and maximize ROI with the SKOPE-connect commercial fridge management app built into every ActiveCore 2 fridge
- Reduce display fridge repair costs and business downtime with the ActiveCore interchangeable refrigeration system for safe, streamlined servicing
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1085 W x 795 D x 2005 H (mm)
- Doors: 2
- Door Type: Glass / Solid
- Shelves: 5 (per door)
- Material: Powdercoat galvanised steel or stainless steel interior & exterior
- Gross Volume (Litres): 880
- Total Floor Area (m²): 0.86
- Weight (kg): 220
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 1°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 99g (natural refrigerant)
- GEMS Class: 3M1
- GEMS Energy Consumption (kWh/24h): 3.46
- GEMS Annual Running Costs: \$379 p.a. (@ \$0.30/kWh)
- kW: 0.72
- Current Draw (Amps): 3.0 (includes unit 2.6)
- Electrical Safety Climate Class: 5
- Interior Lighting: 2 x 1370mm, 15W LED
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Bottom mounted, integral, removable ActiveCore refrigeration unit (UBHCNI-0008)
- Power Cord: Supplied with 2.0m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS

- Black exterior/black interior finish
- Stainless Steel Finish
- White exterior/white interior finish
- Other Colour Within Available SKOPE Range
- Barrel Door Locks
- Branded Decals Print (Sign, Sides & Kick Panel)
- Glass Viewing Panel to Sides
- Gravity Matting
- Internal LED Lighting (for Solid Doors)
- Internal Shelf Lighting
- Lit Sign (See AC Model)
- Merchandising Strips
- Passthrough (Solid Doors)
- Plinth Mounting
- Remote Refrigeration Unit
- S/S Shelves per Cabinet
- Solid Doors
- Tropical Heated Glass