

CS ZP Series Ice Maker CS46 ZP

TECHNICAL SPECIFICATION SHEET FOR

Icematic CS ZP Ice Maker - Self Contained

CS46 ZP Ice cubes 35mm x 37mm x H 32mm, 20g



Ice Maker

- 39kg daily production rate
- **15kg** storage bin capacity
- W 35mm x D 37mm x H 32mm, 20g ice cubes
- 28 ice cubes per cycle
- 3.8 litres per hour water consumption
- Air cooled condensing unit
- Zero Pollution (ZP) uses R290 propane refrigerant gas
- Energy efficient energy saving up to 25%
- Spray system technology to produce patented pure, clear and transparent ice cubes
- Electronic bin level sensor
- Multicolour LED button for machine status standby, cleaning, and optional Ozone cycle
- Automatic Cleaning
- Easy access internal bin pan for easy clean

- Stainless steel external body
- Front ventilation for improved yield even in critical install
- Moffat TA13-NZ filter kit, including head and fittings

Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.







CS ZP Series Ice Maker CS46 ZP

moffat.co.nz

Telephone 09-574 3150 sales@moffat.co.nz

New Zealand

Moffat Limited Christchurch

45 Illinois Drive

Rolleston Christchurch 7675 Telephone 03-983 6600 Facsimile 03-983 6660 sales@moffat.co.nz


Auckland

TECHNICAL SPECIFICATION SHEET FOR


Icematic CS ZP Ice Maker - Self Contained

CS46 ZP

Front view 500mm [19 3/4"] mm [27 1/4"] 774mm [30 1/2"]




Kit 4 Feet Ontional Ø50mm H100-120 mm







Water outlet connection 20 mm



Water outlet connection water condensation 20 mm

Water inlet connection - 3/4" gas

Ice production per 24 hours

Water temperature


Ambient temperature	°C	32°	21°	15°	10°	
	10°	34	41	45	46	kg
	21°	28	34	38	39	kg
	32°	26	32	36	37	kg
	38°	22	30	34	35	kg

CS46 ZP

Dimensions

500mm Width: Height: 690mm Depth: 540mm Nett weight: 38kg Packed weight:

Ice cube production dimension Ice: 35mm x 37mm x H 32mm,



Water consumption Air cooled version: 3.8 litres per hour

Electrical rating

Air cooled version: 220-240V, 1P+N+E, 50Hz

Compressor power rating 1054W Total absorbed power 480W, 10A cordset fitted

Refrigerant type R290

Installation distance from wall

150mm - rear right 50mm

150mm left

Placement of unit should be indoors in an environment that does not exceed the air and water temperature limitations of the unit

Water connection requirements

Inlet connection: R 34' Cold water (5-35°C) Pressure (1-5 bar)

Water outlet connection: Ø 20mm

Note: 3m radius to any source of flame, combustion material or explosive material and ensure sufficient air circulation.

Disclaimer:

All unit capacities are based on subjective testing. Moffat accepts no liability for production values.



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd





an Ali Group Company