

Modular Ice Maker MC132F | MC132H

TECHNICAL SPECIFICATION SHEET FOR

Icematic Modular Ice Maker

MC132F - Full Dice W 22mm x D 22mm x H 24mm, 10g

MC132H - Half Dice W 10mm x D 29mm x H 24mm, 6g



- Full dice (F model) or half dice (H model) sized ice cube machine head only
- 138kg daily production rate
- 168 full dice ice cubes per cycle
- 275 half dice ice cubes per cycle
- Air cooling condensing unit
- Vertical evaporator with circulation pump
- Front baffle with magnetic switch that stops the machine when bin is full
- Electronic control panel with LED showing proper functioning or warning indicators
- Stainless steel external body
- Requires storage bin model SB105, SB155, SB205*, SB255*
- Moffat IM101000 single stage triple action filtration system, including head and brass fittings
- * Cover kit KM 205-255 required to suit with storage bins SB205 and SB255

Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.








Modular Ice Maker MC132F | MC132H

TECHNICAL SPECIFICATION SHEET FOR

Icematic Modular Ice Maker MC132F | MC132H







Full dice ice production per 24 hours

Water temperature

Ambient temperature	ů	32°	21°	15°	10°	
	10°	129	147	150	154	kg
	21°	112	127	133	138	kg
	32°	96	107	110	113	kg
	38°	79	87	95	98	kg

(A) Water drain Ø20 mm

B Potable water inlet 3/4

C Electrical cable supply


MC132F | MC132H

Dimensions

Width: 560mm
Height: 575mm
Depth: 620mm
Nett weight: 53kg
Packed weight: 65kg

Ice cube production dimension

Full dice: W 22mm x D 22mm x H 24mm, 10g Half dice: W 10mm x D 29mm x H 24mm, 6g



Water consumption

Air cooled condensing unit: 7 litres per hour

Refrigerant type R404a

Electrical rating

220-240V, 1P+N+E, 50Hz Compressor power rating 1637W Total absorbed power 850W 10A cordset fitted

Installation distance from wall

- rear 150mm - right 150mm

- left 150mm

Placement of unit should be indoors in an environment that does not exceed the air and water temperature limitations of the unit

Water connection requirements

Inlet connection: R ¾" Cold water (5-35°C) Pressure (1-5 bar)

Water outlet connection: Ø 20mm





moffat.com.au moffat.co.nz

Australia

Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia

Telephone 03-9518 3888 vsales@moffat.com.au

Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone 08-9202 6820 bgarcia@moffat.com.au

New Zealand Moffat Limited

Christchurch

45 Illinois Drive Rolleston Christchurch 7675 Telephone 03-983 6600 Facsimile 03-983 6660 sales@moffat.co.nz

Auckland

Telephone 09-574 3150 sales@moffat.co.nz

Disclaimer:

All unit capacities are based on subjective testing. Moffat accepts no liability for production values.



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd Moffat 12.14



