


Two Glass Swing Door BackBar

Range: BackBar SKOPE ID: BB002

Dimensions: 1480mm (W) × 590mm (D) × 1025mm (H)*

Capacity: 410L

* Height with castors is adjustable from 1015 to 1030.





A glass door under-bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The 'frameless' glass doors provide maximum product viewing and are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. For high humidity tropical environments heated glass versions are available. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.




















Cabinet

Туре	BackBar		
Finish	Powdercoat galvanised steel or stainless steel		
	Туре	PU foam	
Insulation	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso Pentane (C5H10/C5H12)	
	Type	Glass swing door (double-glazed, low-e, argon-filled)	
Doors	Opening Size	Height (mm) 730	
		Width (mm) 460	
Chabina	Four adjustable height, plastic-coated wire shelves		
Shelving	$4 \times$ outer shelf (497W \times 440L)		
Lighting*	$1 \times 16W$ dimmable, cool white (5500-6500K) LED strip on cabinet ceiling		

Dimensions[†]

	External	Internal	Packed
Width (mm)	1480	1020	TBC
Depth (mm)	590	530	TBC
Height (mm)	1025 (std. castors) 920 (plinth mount)	758	TBC
Weight (kg)	180		TBC
Capacity (L)	410		
Footprint (m ²)	0.87		

Ventilation (mm) Top Not required

Product Loading					
Facing	330ml can	28	600ml bottle	28	
Loading	330ml can	168	600ml bottle	168	

Not required

Rear

Not required

Sides

* Accessible via the free SKOPE-connect[™] app.

† Allow for dimensional tolerances when installing the cabinet(s).

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* f	rom 0 to 15)
Rated Ambient Temperature	32°C/65% relative h	umidity
Maximum Ambient Temperature (°C)	40	
Sound Lovel (dP(A))	Standard	<66
Sound Level (dB(A))	Hush Mode*	<62

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	9
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	2.1 kWh/24h
Annual Running Costs	\$229.95 (@ \$0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9m power cord with 3-pin, 10 amp plug
Current draw (A)	1.7

Refrigeration

3	
Controller	SCS Connect (SKOPE-connect™ compatible)
System Type	Removable cartridge
Cartridge Weight (kg)	24
Refrigerant/Charge	R290/81g
Nominal Capacity (W)	650
Heat Rejection (W)	Average 90 Peak 110
Remote Duty	n.a.
Defrost Type	Off-cycle
Drainage	No plumbing required



BB.2.GSW on the SKOPE website



