



ProSpec 1 Solid Door Upright GN 2/1 Freezer

Model ID: PG21.UPF.1.SD

Heavy-duty gastronorm flexibility in an ultra-tough, premium 304 stainless steel one solid door freezer. Transfer pans with ease in a package offering the very best in SKOPE engineering for busy venues, from natural refrigerant technology to easy-clean design features.



2 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Full 304 stainless steel design and build
- 5 x GN 2/1 stainless steel racks on adjustable/removable supports: 65mm D / 16 pans, 100mm D / 11 pans, 150mm D / 7 pans, 200mm D / 6 pans
- SKOPE-connect™: control temperature from your smartphone with easy pre-sets and food safety security features
- Minimize costs and carbon footprint with natural refrigerant technology
- Easy-to-service ActiveCore™ removable refrigeration cartridge system
- Premium-look contemporary design promotes usability and modern working environment for staff
- Door activated interior lighting, pre-fitted barrel locks and coved internal floor
- GEMS compliant

SPECIFICATIONS

- Dimensions: 730 W x 865 D x 2185 (with castors - adjustable from 2185 to 2200) or 2245 with legs H (mm)
- Doors: 1
- Door Type: Solid
- Shelves: Five adjustable height, stainless steel GN 2/1 shelves (530W x 650L)
- Material: 304 AISI stainless steel
- Gross Volume (Litres): 572
- Total Floor Area (m²): 0.63
- Weight (kg): 164
- Refrigeration Unit: Self-Contained
- Temperature Range: -21 to -18 (adjustable with SKOPE-connect -26 to -12)
- Max Ambient Temperature: 40
- Refrigerant: R290 / 107g
- GEMS Class: 5L1
- GEMS Energy Consumption (kWh/24h): 7.98
- GEMS Annual Running Costs: \$874 (@ \$0.30/kWh)
- Current Draw (Amps): 5.5
- Noise Measurement (dB): Standard 64 Hush Mode (via SKOPE-connect) 62
- Interior Lighting: 1 x 1400mm, 16 watt LED light (door-activated)
- Controller: SCS Connect (SKOPE-connect™ compatible)
- Refrigeration System: Removable cartridge
- Power Cord: 3m power cord with 3-pin, 10 amp plug
- Power Supply: 220-240 volts a.c., 50Hz, single phase supply

OPTIONS

- Extra Runners
- Extra S/S Shelf
- Extra Shelf & Slides