



ProSpec 2 Solid Door Upright GN 2/1 Fridge

Model ID: PG21.UPR.2.SD

ProSpec offers chefs, consultants and architects a high-performance gastronorm solution. All the features of the award-winning ReFlex series but with a cutting edge look and an upgrade to ActiveCore™ swappable cartridges.



5 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, poultry, red meat, fresh seafood, live seafood, dairy and desserts temperature ranges
- Full 304 Stainless Steel body and SKOPE design quality ensure tough durability for back of house duties
- Minimise costs and carbon footprint with natural refrigerant technology
- Easy-to-service ActiveCore™ removable refrigeration cartridge system
- Premium-look contemporary design promotes usability and modern working environment for staff
- Includes 5 x GN 2/1 stainless steel racks on adjustable and removable stainless steel supports: 65mm D / 32 pans, 100mm D / 22 pans, 150mm D / 14 pans, 200mm D / 12 pans
- Door activated interior lighting, pre-fitted barrel locks and coved internal floor
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1410 W x 865 D x 2185-2200 H (mm)
- Doors: 2
- Door Type: Self-closing, lockable, solid swing door with stay open position at 90°C
- Shelves: 5 stainless steel GN 2/1 adjustable wire shelves per door on a fully removable and cleanable racking system
- Material: 304 AISI stainless steel interior and exterior on all faces
- Gross Volume (Litres): 1266
- Total Floor Area (m²): 1.21
- Weight (kg): 230
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 1°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 99g (natural refrigerant)
- GEMS Class: 5M1
- GEMS Energy Consumption (kWh/24h): 3.91
- kW: 0.72
- Current Draw (Amps): 3.0 (includes unit 2.6)
- Electrical Safety Climate Class: 5 (40°C/40% RH)
- Interior Lighting: 2 x 1400mm, 16W LED light (door activated)
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Top mounted, integral, removable ActiveCore refrigeration unit (UTHCNI-0010)
- Power Cord: Supplied with 2.3m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS

- Extra Runners
- Extra S/S Shelf
- Extra Shelf & Slides